EF5500DE/D



EF5500D \$1,249 MSRP



EF5500DE \$1,399 MSRP

TOP FEATURES:

- **1.** Reduced price, more wattage Great value with the same legendary quality and performance.
- **2.** The EF5500DE comes with an electric starter and auto choke for effortless push button starting.
- ${f 3}$. Comes standard with wheels, fold-down/locking handles and battery.
- 4. Eight hours run time at full load -13% longer run time than previous model.
- **5.** Digital Hour Meter, Digital Volt Meter displays total run time accumulation for servicing and indicates the voltage output.
- ${\bf 6.}$ 3 year industrial and residential warranty with optional Y.E.S. for customer peace of mind.
- 7. Lifting eye convenient for hoisting and security.
- **8**. OHV engine offers efficiency, increased reliability, and quieter operation.
- **9.** Full power, full time 120/240 dual voltage is ideal for the job site or home backup.
- **10.** Ground Fault Circuit Interruption (GFCI) senses a leak to ground to reduce risk of electric shock.
- **11**. Fuel gauge provides easy monitoring of fuel level.
- **12.** The EF5500D/DE features a rugged design with full roll cage protection for heavy jobs.



EF5500DE/D

FEATURES & BENEFITS

FEATURES:

New and improved OHV MZ360 engine with a hemispherical head
— Yamaha legendary durability and reliability

Rugged Wheel kit w/fold-down locking handles — Standard on EF5500DE and EF5500D

The battery is standard on the EF5500DE — Wheel kit and Battery are a great value and offer added convenience for transport and starting

Cast iron cylinder lining — Optimal heat dissipation

Automatic oil warning system shuts off engine before oil level is low — Prevents engine damage, avoids costly repairs, minimizes down time, enhances long term durability

Transistorized ignition provides lean, efficient spark — Maintenance-free and ensures fast, easy starting, reliable operation

Auto decompression — Automatically "opens" exhaust valve to reduce compression for easier starting

EPA Emission Engine Life Rating — The EF5500DE and EF5500D meet the strictest environmental standards - EPA and CARB

Ground Fault Interrupter (G.F.I.) — If the system senses a leak to "ground," it automatically cuts off power to help prevent injuries

Fuel gauge — Lets operator monitor how much fuel is left

Tool kit — Makes service easier

AVAILABLE ACCESSORIES & OPTIONS:

Wired Remote Kit — Features a 33-foot cord with remote starter switch

Yamaha Extended Service — Additional 1, 2 or 3 years of Y.E.S. is available

yamahamotorsports.com

For Accessories, visit shopyamaha.com

SPECIFICATIONS:

Type Dual voltage, Brushless, AC Generator

Maximum AC Output 5500 watts

Rated AC Output 4500 watts

Rated / Maximum AC Rated / Maximum AC Current 36.0 / 44.0 amps @

Current 120V - 18.75 / 22.9 amps @ 240V

EngineMZ360Displacement358ccOverall Length31.5 inOverall Width28.4 in

Overall Height 29.1 in (handle down)

Dry Weight D = 212 lb, DE = 234 lb

Fuel Tank Capacity 6.9 gal **Continuous Operation** 9.0 hr

at Rated Load

Noise Level 74.1 dBA

Warranty 3 Years Limited Warranty

Color EF5500D; EF5500DE

Specifications subject to change without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement. © 2016 Yamaha Motor Corporation, U.S.A. All rights reserved.

^{***} Wet weight includes the vehicle with all standard equipment and all fluids, including oil, coolant (as applicable) and a full tank of fuel. It does not include the weight of options or accessories. Wet weight is useful in making real-world comparisons with other models.